

DW156

Description

Apparecchio ad incasso per interni, a scomparsa per controsoffitti in gesso, telaio in alluminio. LED COB ad alto rendimento. Disponibile a 7W, 12W, 18W e varie colorazioni, cri 80, lente 36°


3100K

CRI	Ra 80
Lumen	1000lm , 1700lm , 500lm
Led Type	COB
Brand Led	Bridgelux
Ref.	37
Power supply	100,0-280,0Vac
Hole	75x75mm , Q0850 , 60x60mm
Packaging	Box
Warranty	2 years
Finishes	Nero RAL9005 , Bianco RAL9010

Comparison of models

	Finishing	Input power supply	Number of LEDs	Color light	Ref.	Lumen
DW156-12-BBC	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BBN	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BCC	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BCN	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BGC	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BGN	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BIC	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BIN	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BWC	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-BWN	Nero RAL9005	100,0-280,0Vac	1	C	37	1000lm
DW156-12-REFB						
DW156-12-REFC						
DW156-12-REFG						
DW156-12-REFI						
DW156-12-REFW						
DW156-12-WBC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm

DW156-12-WBN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WCC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WCN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WGC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WGN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WIC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WIN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WWC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-12-WWN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1000lm
DW156-18-BBC	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BBN	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BCC	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BCN	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BGC	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BGN	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BIC	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BIN	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BWC	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-BWN	Nero RAL9005	100,0-280,0Vac	1	C	37	1700lm
DW156-18-REFB						
DW156-18-REFC						
DW156-18-REFG						
DW156-18-REFI						
DW156-18-REFW						
DW156-18-WBC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WBN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WCC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WCN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WGC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WGN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WIC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WIN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WWC	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-18-WWN	Bianco RAL9010	100,0-280,0Vac	1	C	37	1700lm
DW156-7-BBC	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BBN	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BCC	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BCN	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BGC	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BGN	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BIC	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BIN	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BWC	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-BWN	Nero RAL9005	100,0-280,0Vac	1	C	37	500lm
DW156-7-REFB						
DW156-7-REFC						
DW156-7-REFG						
DW156-7-REFI						
DW156-7-REFW						
DW156-7-WBC	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WBN	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WCC	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WCN	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WGC	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WGN	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WIC	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WIN	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WWC	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm
DW156-7-WWN	Bianco RAL9010	100,0-280,0Vac	1	C	37	500lm